TÜV-Verband Welding Consumable Leaflet

according to TÜV-Verband Technical Leaflet 1153 and DIN EN 14532

TÜV VERBAND	DAIKO S. Viale Fe	turer/Supplier R.L. Plissent, 84/D 00 Treviso (TV)						2 Number: 19539.02 29.09.202	25
3 Welding consumable*:		Drahtelektrode							
4 Trade name*	:	DAIKOWM 2209							
7 Type*:		EN ISO 14343-A - G 22 9 3 N L							
11 Diameter ra	nge:	0,8 bis 1,6 mm							
12 Auxiliary ma	terials:	EN ISO 14175	- M 13	3					
13 The validity	is certified by th	ne appearance of the	weldin	g consumal	ole leafl	et in the welding	g consumables	oortal.	
15 Materials an	nd postweld hea	at treatment							
Pos Wb Group / Material 1				Text		Group / Materia	al 2		Remarks
U Gruppe 10.1 (Duplex)									
16 Material groups acc. to CR ISO 15608									
21 Root weldability: not verified									
23 Wall thickness: max. 40 mm									
24 Type of current and polarity: G+									
25 Welding position according to DIN EN ISO 6947:1997-05: PA, PC									
26 Highest operating temperature in the short-term range as for parent metal, but not higher than:									
27 Highest ope	rating temperat	ture in the long-term	nax.:			°C			
28 Lowest oper	rating temperat	ure/as for parent met	not lower th	an:		-80 °C			
29 Design stress value/as for parent metal: wie Grundwerkstoff									
30 For use in the	ne long-term rai	nge:							
31 Resistance to intergranular corrosion proven in accordance with:					ISO 36	51-2			
32 Remarks:									
EN 14532. If no	conflicting tes	elding consumable w t principles are stated ipment Directive 201	d under	heading 32	- Rem				
34 Explanations		pered tion annealed and quenched malized	S stress- St stabiliz U non-ar V harder	zed		W soft annealed	G- dire	ect current plus pole ect current minus pole rnating current	Э
35 Compiled in	accordance wi	th the data of:	NORD	Gruppe					
		te edition by photomechanical of Stein, 51105 Köln - Unternehme				he editor's approval eve	en if only used in extract	s. Editor: TÜV-Verba	and e. V.